

Fitment Instructions

Model: Nissan Navara D40

Underbody Protection Plate

Part Number: IUP007E

Engine Bay

Years: 2005 -

Engine type: 2.5 dCi, 2.5 dCi (4WD)

APPLICATION:

Protection of engine bay and transmission elements from damage. Protection of engine bay and transmission elements from dust and water.

INSTALLATION:

This protection plate has been designed for installation to the intended application only. It should be mounted according to these installation instructions by an experienced Ironman 4x4 dealer or certified fitter. The plate is fixed to original vehicle mountings located on the vehicle's body load-bearing elements. Upon successful installation the plate should not interfere with any other parts or components.

INSTALLATION MANUAL:

- 1. Install threaded inserts into the front subframe.
- 2. Install the plate to the vehicle using the threaded inserts.
- 3. Tighten all screw joints.

WARRANTY:

Warranty period - 12 Months

WARRANTY TERMS:

The plate should only be installed on a vehicle with undamaged body and load-bearing elements, vehicles which have been involved in a significant collision may prevent successful installation.

Ironman 4x4 does not bear liability for any damages caused to the vehicle, or injury to persons in case of installation or product failure. Ironman 4x4 has a right to introduce changes into the skid plate construction.




The Quality Management System at production has been audited by Bureau Veritas Certification and conforms to requirements of the ISO 9001:2008 standard.

www.ironman4x4.com

IRONMAN 4X4 MELBOURNE SHOWROOM Cnr Centre & Westall Roads, Clayton, Victoria 3168

Telephone +61 3 9532 1111

IRONMAN 4X4 BRISBANE SHOWROOM 1 Hinkler Court Brendale, QLD, 4500 Telephone (07) 3482 9500 IRONMAN 4X4 PERTH SHOWROOM Unit 9/511 Abernethy Road Kewdale, WA, 6105 Telephone (08) 6254 4444



LIST OF PARTS

NO.	NAME					
1	Tailed threaded insert	3				
2	Tailed threaded insert	1				
3	Washer 8	4				
4	Bolt M8x20	4				

Thread	M6x1.0	M8x1.25	M10x1.5	M12x1.75
Tightening torque	9.8 Nм	24.0 Nм	47.0 Nм	81.0 Nм